

Client/Team	
Serial #	
Application	
Assembly Specs	
Special Notes	
NEW / DEMO	

MainShaft Hub E/F	
Shims Thickness:	
Notes:	

M/S Cover Depth	
M/S Length Case	
E/F	
Shim Thickness	
Final E/F - Preload	
Notes:	

L/S Cover Depth	
L/S Length Case	
Gear Offset	
E/F	
Shim Thickness	
Final E/F - Preload	
Notes:	

XD Version	4XD / 5XD	6XD/6XDX
STD / TA version	STD	TA
Front Cover Version	STD / Vette	Hewland
Shifter Hsg Gen	Tall or Flipped	Low
Shifter Boot	Vynl	Fire Sock
MME or Motec Air	No	Yes
Handle / Straight	2" / 3"	5" / 8"
Hi Res Load-Cell	No	Yes
Slider version	6	8
6 to 8 Lug - Slider	No	Yes
Input		
Oil Pump Version	STD	TA
Display Housing	No	2 / 3
Display Harness	No	Yes
Lock-Out Harness	No	Yes
Additional Items:		
Dyno Notes:		

Additional Notes:	

Gear Ratio Status:	*	Blue Gear Set Currently Available	*
	*		*
	*	Gear Sets NOT available currently	*
	*	"W" = 2000 ftlbs WIDE Headsets & 1st Gearsets	*

"W" = 2000 ftlbs Spec										
DROP Gear Head Sets		Input Cluster Ratio		AP	AP	AP	AP	AP	AP	AP
				23/21w	23/23w	21/22w	21/23w	20/23w	20/24w	21/26w
				23	23	21	21	20	20	21
				0.913	1.000	1.048	1.095	1.150	1.200	1.238
				WIDE	WIDE	WIDE	WIDE	WIDE	WIDE	WIDE

34	15	2.267	w	A	P	1st Gear Only 32 Spline L/s Gear	2.070	2.267	2.375	2.483	2.607	2.720	2.806	2.914	3.022	3.173	
38	17	2.235					2.041	2.235	2.342	2.448	2.571	2.682	2.768	2.874	2.980	3.129	
33	15	2.200	w	A	P		2.009	2.200	2.305	2.410	2.530	2.640	2.724	2.829	2.933	3.080	
32	15	2.133	w	A	P		1.948	2.133	2.235	2.337	2.453	2.560	2.641	2.743	2.844	2.987	
38	18	2.111	w	A	P		1.928	2.111	2.212	2.312	2.428	2.533	2.614	2.714	2.815	2.956	
31	15	2.067	w	A	P		1.887	2.067	2.165	2.263	2.377	2.480	2.559	2.657	2.756	2.893	
30	15	2.000	w	A	P		1.826	2.000	2.095	2.190	2.300	2.400	2.476	2.571	2.667	2.800	
29	15	1.933			A		P	1.765	1.933	2.025	2.117	2.223	2.320	2.394	2.486	2.578	2.707
28	15	1.867						1.704	1.867	1.956	2.044	2.147	2.240	2.311	2.400	2.489	2.613
29	16	1.813			A		P	1.655	1.813	1.899	1.985	2.084	2.175	2.244	2.330	2.417	2.538
28	16	1.750	w	A	P		1.598	1.750	1.833	1.917	2.013	2.100	2.167	2.250	2.333	2.450	
27	16	1.688			A	P	1.541	1.688	1.768	1.848	1.941	2.025	2.089	2.170	2.250	2.363	
28	17	1.647					1.504	1.647	1.725	1.804	1.894	1.976	2.039	2.118	2.196	2.306	

Pawl Brg Stacked	Yes / No	Loctite	Case Gen:	1	2 multihole	
Shifter Barrel Wired	Yes	No	Tail Hsg Gen:	STD	VETTE	T/A
			Front Cover Gen:	Breather	No Brthr	Special
			Pawl Cover	Relieved		
			Pawl Spring:	.080		
			Detent Spring:	.072		
			Flat Roller Brgs	Input	L/S	RoadRace
			Ball Bearing	M/S	L/S	
			Hub Spec:	Solid		Solo

6XD BUILDER	Head Set:	1st Gear	2nd Gear	3rd Gear	4th Gear	5th Gear	6th Gear
	Gear Set#						
REAR Gear Ratio:	Trans Ratio						
	Max RPM						
DATE Built:	MPH						
	RPM Drop						

Max RPM:		Configuration NOTES:	
Peak HP RPM:			
Tire Diameter:			
Tire Circumference			